

Panel mounted receptacle
Part no. 1551




- screw terminals
- 20° inclination
- receptacles optional fitted with auxiliary contact

Technical specifications

Ampere	32 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP67
Flange	100x92 mm
Fixing hole	85x77 mm
Inclination	20 °
Weight	334 g
Certifications	VDE

Drawing



Drawing		16			32		
1 MB 251		Poles			Poles		
Dim. in mm		3	4	5	3	4	5
a	73.5	100	100	100	100	100	100
b	64	92	92	92	92	92	92
c	52	60	62	64	64	66	
d	60	85	85	85	85	85	
e	52	77	77	77	77	77	
f	5.5	5.5	5.5	5.5	5.5	5.5	
g	8	8	8	8	8	8	
g.1	2	2	2	2	2	2	
h	84	100	105	109	109	113	
i	78	85	96	103	103	110	
k	49	32	32	53	53	45	
l	52	55	65	67	67	72	
l1	60	63	72	82	82	85	
a	20°	20°	20°	20°	20°	20°	
Terminal for cond. cross		1.5	1.5	1.5	2.5	2.5	2.5
section (mm²) min.-max.		—4	—4	—4	—10	—10	—10