

Product datasheet

Specifications



Kaedra - for power outlet - 4 openings - 1 x 8 modules

13179

Main

Range	Mureva
product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
9 mm pitches	16
Number of 18 mm modules per row	8
Total number of 18 mm modules	8
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Number of openings of interface	4
Number of plates	1 for push-button controls 4 for 65 x 85 power outlets
Provided equipment	2 wiring strap 1 plate for push-button control 4 plate for 65 x 85 power outlet
Type of front cover	Transparent
Power dissipation in W	15 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Locking options description	Optional keylock
Enclosure material	Housing: self-extinguishing polymer
Net weight	2 kg
Base dimension	90 x 100 mm
Width	236 mm
Height	460 mm
Depth	160 mm
Internal depth	91 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Colour	Door: transparent green Enclosure: light grey (RAL 7035)
--------	---

Environment

Standards	EN 62262 IEC 61439-3 EN 50262 IEC 60695-2-1 IEC 60670
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.4 cm
Package 1 Width	26.3 cm
Package 1 Length	47.3 cm
Package 1 Weight	1.96 kg
Unit Type of Package 2	P12
Number of Units in Package 2	42
Package 2 Height	117.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	96.924 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	11
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Minimum percentage of recycled plastic content	25
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5036b720-908f-495f-9f9e-e215274e05b0
REACH Regulation	REACH Declaration
Halogen content performance	Halogen free product

Use Again

Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No