

# Product datasheet

Specifications



## Kaedra - for power outlet - 6 openings - 1 x 12 modules

13181

### Main

|                            |                            |
|----------------------------|----------------------------|
| Range                      | Mureva                     |
| product name               | Mureva Enclosure           |
| Product or component type  | Weatherproof enclosure     |
| Enclosure type             | Enclosure for power outlet |
| Mounting plate description | Without mounting plate     |

### Complementary

|                                 |                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------|
| Enclosure mounting              | Surface                                                                               |
| 9 mm pitches                    | 24                                                                                    |
| Number of 18 mm modules per row | 12                                                                                    |
| Total number of 18 mm modules   | 12                                                                                    |
| Number of horizontal rows       | 1                                                                                     |
| Electrical insulation class     | Class II<br>Double insulation                                                         |
| Number of openings of interface | 6                                                                                     |
| Number of plates                | 2 for push-button controls<br>6 for 65 x 85 power outlets                             |
| Provided equipment              | 2 wiring strap<br>6 plate for 65 x 85 power outlet<br>2 plate for push-button control |
| Type of front cover             | Transparent                                                                           |
| Power dissipation in W          | 28 W                                                                                  |
| [In] rated current              | 63 A                                                                                  |
| Type of rail                    | DIN                                                                                   |
| Number of pre-cutouts PG ISO    | 17                                                                                    |
| Locking options description     | Optional keylock                                                                      |
| Enclosure material              | Housing: self-extinguishing polymer                                                   |
| Net weight                      | 2.5 kg                                                                                |
| Base dimension                  | 90 x 100 mm                                                                           |
| Width                           | 340 mm                                                                                |
| Height                          | 460 mm                                                                                |
| Depth                           | 160 mm                                                                                |
| Internal depth                  | 91 mm                                                                                 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|        |                                                             |
|--------|-------------------------------------------------------------|
| Colour | Door: transparent green<br>Enclosure: light grey (RAL 7035) |
|--------|-------------------------------------------------------------|

## Environment

|                                       |                                                                                                                 |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Standards                             | IEC 61439-3<br>IEC 60695-2-1<br>IEC 60670<br>EN 62262<br>EN 50262                                               |
| Fire resistance                       | 650 °C conforming to IEC 60695-2-1                                                                              |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                    |
| IK degree of protection               | IK09 conforming to EN 50102                                                                                     |
| Environmental characteristics (UV)    | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage category                  | II                                                                                                              |
| Ambient air temperature for operation | -25...40 °C                                                                                                     |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 16.8 cm   |
| Package 1 Width              | 36.0 cm   |
| Package 1 Length             | 47.0 cm   |
| Package 1 Weight             | 2.848 kg  |
| Unit Type of Package 2       | P12       |
| Number of Units in Package 2 | 28        |
| Package 2 Height             | 80.0 cm   |
| Package 2 Width              | 80.0 cm   |
| Package 2 Length             | 120.0 cm  |
| Package 2 Weight             | 91.744 kg |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

| Environmental footprint                               |                                               |
|-------------------------------------------------------|-----------------------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 15                                            |
| Environmental Disclosure                              | <a href="#">Product Environmental Profile</a> |

Use Better

| Materials and Substances                       |                                                            |
|------------------------------------------------|------------------------------------------------------------|
| Minimum percentage of recycled plastic content | 25                                                         |
| Packaging made with recycled cardboard         | No                                                         |
| Packaging without single use plastic           | No                                                         |
| <a href="#">EU RoHS Directive</a>              | Pro-active compliance (Product out of EU RoHS legal scope) |
| REACH Regulation                               | <a href="#">REACH Declaration</a>                          |
| Halogen content performance                    | Halogen free product                                       |

Use Again

| Repack and remanufacture |                                          |
|--------------------------|------------------------------------------|
| Circularity Profile      | No need of specific recycling operations |
| Take-back                | No                                       |