

Product datasheet

Specifications



Kaedra - for power outlet - 1 openings - 1 x 5 modules

13185

Main

Range	Mureva
product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for power outlet
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
9 mm pitches	10
Number of 18 mm modules per row	5
Total number of 18 mm modules	5
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Number of openings of interface	1
Type of front cover	Transparent
Power dissipation in W	12 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Locking options description	Optional keylock
Enclosure material	Housing: self-extinguishing polymer
Net weight	1.2 kg
Base dimension	103 x 225 mm
Width	138 mm
Height	460 mm
Depth	160 mm
Internal depth	91 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	EN 62262 IEC 60670 IEC 61439-3 IEC 60695-2-1 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	47.000 cm
Package 1 Width	15.800 cm
Package 1 Length	16.800 cm
Package 1 Weight	1.408 kg
Unit Type of Package 2	P12
Number of Units in Package 2	66
Package 2 Height	80.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	104.928 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	7
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Minimum percentage of recycled plastic content	27
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5036b720-908f-495f-9f9e-e215274e05b0
REACH Regulation	REACH Declaration
Halogen content performance	Halogen free product

Use Again

 Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No