



# 2330 G3 M73 PW19 3600-840 ETWD

## Recessed LED luminaire

TOC: 7631765



## Product description

### Luminaire type

Square recessed LED ceiling luminaire with prismatic PMMA cover. Version M73 (600 mm x 600mm).

### Light management

Suitable for control via smartphone/tablet with LiveLink Basic Wireless app (iOS and Android).

### Applications

Offices, Corridors, Foyers, Conference rooms, Retail areas, waiting zones.

### Mounting methods

For system ceilings with exposed grids.

### Optical system

PMMA cover with microprisms. With symmetric limited wide light distribution. Glare evaluation according to UGR rating (EN 12464-1) < 19. Suitable for VDU workstations according to EN 12464-1 via limited luminance  $L \leq 3000 \text{ cd/m}^2$  for beam angle above  $65^\circ$  all-round. Harmonious light effect due to homogeneously illuminated light emission.

### LED system

Luminaire luminous flux and light color fixed. Luminaire luminous flux 3600 lm, connected load 31 W, Power Faktor  $\lambda > 0,95$ , maximum luminous efficiency of luminaire 116 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 5 \text{ SDCM}$ . Mean rated service life  $L65(t_q 25^\circ\text{C}) = 50,000 \text{ h}$ .

### Luminaire body

Luminaire body of aluminium. Surface coated white (RAL 9016). Dimensions (L x W): 595 mm x 595 mm, luminaire height 65 mm. Safety class (EN 61140): II, protection rating (DIN EN 60529): IP20, Protection rating on room side: IP40, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11:  $650^\circ\text{C}$ . Weight: 2,2 kg.

### Electrical version

With electronic control gear unit, wirelessly dimmable via compatible systems (app / push-button). Control gear unit according to DALI-2 standard (EN 62386). Luminaire is switchable and dimmable by means of touch functionality via DALI control terminals (Touch DIM). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol. The luminaire is also ENEC-certified by an independent testing authority.

Disassembly instructions (PDF) for the product available at: <https://www.trilux.com/EcoDesign>

## Product features and key data

<b>Applications</b>	Offices Corridors Foyers Conference rooms Sales rooms Waiting zones
<b>Luminaire type</b>	Square recessed LED ceiling luminaire with prismatic PMMA cover.
<b>Mounting method</b>	Recessed
<b>Luminaire optic</b>	PMMA cover with microprisms.
<b>Light Engine</b>	standard product
<b>Colour temperature</b>	4000 K
<b>Rated luminous flux</b>	3600 lm

## Product features and key data

Connected load	31,00 W
Luminous efficacy	116 lm/W
Service life	L65 (25 °C) = 50.000 h
Colour rendering index	80
Colour tolerance	5 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL9016 Traffic white
Luminaire body	Luminaire body of aluminium.
Electrical version	With electronic control gear unit, wirelessly dimmable via compatible systems (app / push-button).
DALI-2-Standard EN 62386	Yes
Wire diameter	1,50 mm <sup>2</sup>
Connection method	Plug-in terminal
Touch-Dim-capable	Yes
Dimming range	1 - 100 %
Mains frequency	50/60 Hz
Mains voltage	220 - 240 V
Total harmonic distortion < %	14 %
Ingress Protection (IP) rating	IP20
Protection rating on room side	IP40
Protection class	II
Impact resistance (IK)	IK02
Hot wire resistance	650 °C
Ambient temperature	25 °C
Max. Luminaires B10	31
Max. Luminaires B16	50
Max. Luminaires C10	52
Max. Luminaires C16	85
Net length	595 mm
Net width	595 mm
Net height	65 mm
Recess length	595 mm
Recess width	595 mm
Recess depth	190 mm
Weight	2,2 kg

## Available accessories

Material	Description
7918300	

## EPREL - European Product Registry for Energy Labelling

Energy Efficiency Class

Model identifier

D

S10229193A

## For more sustainability in day-to-day business

New  
packing



CO<sub>2</sub> OPTIMISED



NO PLASTIC



ONLY ONE MATERIAL



100% RECYCLABLE



[www.trilux-twenty3.com/eco](http://www.trilux-twenty3.com/eco)