



## 2360 LED

### Suspended LED luminaire

- VDU workstation compliant (UGR < 19)
- Direct/ indirect illumination

**The 2360 LED is the smart suspended luminaire for standard-compliant lighting e.g. in offices, meeting rooms, banks, schools and educational facilities. This will get the job done!**

### Why you'll get the job done with the 2360 LED suspended luminaire

- Pleasant light effect thanks to uniform illumination with direct and indirect light output
- Especially for VDU workstations (UGR <19)
- 1:1 replacement of conventional luminaires offering time and cost savings during refurbishment.
- High efficiency (115 lm/W).
- Reliable service life (50,000 h, L70).
- Attractive price-performance ratio

### 2360 LED at a glance

|  |  |
|--|--|
| <b>Dimensions</b>                      | H1 1.195 x 295 x 16 mm<br>H2 1.495 x 295 x 20 mm |
| <b>Luminaire luminous flux</b>         | H1 4.400 lm<br>H2 6.000 lm                       |
| <b>Colour Temperature</b>              | Ra > 80 / 3.000 K, 4.000 K                       |
| <b>Connected load</b>                  | H1 40 W<br>H2 52 W                               |
| <b>Protection rating, Safety class</b> | IP20 / IK02 / I                                  |
| <b>Weight</b>                          | H1 5,3 kg<br>H2 6,0 kg                           |
| <b>Lifetime</b>                        | 50.000 h (L70)                                   |

## All variants of 2360 LED

| product reference             | TOC     | Luminous flux [lm] | Wattage [W] | Light colour [K] | Dimensions LxWxH [mm] | Replacement         |
|-------------------------------|---------|--------------------|-------------|------------------|-----------------------|---------------------|
| <b>Switchable</b>             |         |                    |             |                  |                       |                     |
| 2360 H1 PW19-IL 4000-830 ET   | 7377540 | 4.400              | 40          | 3.000            | 1.195 x 295 x 16      | 1 x 54 W / 2 x 28 W |
| 2360 H1 PW19-IL 4000-840 ET   | 7377640 | 4.400              | 40          | 4.000            | 1.195 x 295 x 16      | 1 x 54 W / 2 x 28 W |
| 2360 H2 PW19-IL 6000-830 ET   | 7789940 | 6.000              | 55          | 3.000            | 1.495 x 295 x 20      | 2 x 35 W            |
| 2360 H2 PW19-IL 6000-840 ET   | 7790040 | 6.000              | 55          | 4.000            | 1.495 x 295 x 20      | 2 x 35 W            |
| <b>DALI dimmable</b>          |         |                    |             |                  |                       |                     |
| 2360 H1 PW19-IL 4000-830 ETDD | 7377551 | 4.400              | 40          | 3.000            | 1.195 x 295 x 16      | 1 x 54 W / 2 x 28 W |
| 2360 H1 PW19-IL 4000-840 ETDD | 7377651 | 4.400              | 40          | 4.000            | 1.195 x 295 x 16      | 1 x 54 W / 2 x 28 W |
| 2360 H2 PW19-IL 6000-830 ETDD | 7789951 | 6.000              | 55          | 3.000            | 1.495 x 295 x 20      | 2 x 35 W            |
| 2360 H2 PW19-IL 6000-840 ETDD | 7790051 | 6.000              | 55          | 4.000            | 1.495 x 295 x 20      | 2 x 35 W            |

All technical data as well as weight details and dimensions are carefully created. Errors are not excluded. Product pictures are an example and may differ from the original. We reserve the right to make changes that serve progress.