

2370 LED

Post-top luminaire

- Simple installation
- Multilumen
- Asymmetric wide light distribution

The 2370 LED is a post-top luminaire for lighting traffic roads, bicycle paths, pedestrian crossings, parking lots as well as factory roads. With two sizes and adjustable luminous flux, it offers ideal features for many applications. Universal post fixing for post-top and bracket-mounting. With it you'll do a great job!

Why you'll do a great job with the 2370 LED post-top luminaire

- Flexible setting of luminaire luminous flux due to multilumen
- Simple installation due to adjustable post mounting
- Time- and cost-saving 1:1 LED refurbishment solution
- Efficient illumination due to lens optics with asymmetrical wide distribution characteristic
- Service life 75,000 h (L80)

2370 LED at a glance

Dimensions	488 x 287 x 103 mm 705 x 331 x 113 mm
Luminaire luminous flux	7.500 lm, 4.200 lm, 1.800 lm (Multilumen) 20.000 lm, 15.000 lm, 10.000 lm (Multilumen)
Colour Temperature	3.000 K, 4.000 K
Connected load	62 W / 35 W / 15 W 166 W / 125 W / 83 W
Protection rating, Safety class	IP66 / IK08 / II
Weight	4,5 8,1

All variants of 2370 LED

product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
2370 AB21L/18/42/75/ML-730 ET 26	8260540	7.500 / 4.200 / 1.800	62 W / 35 W / 15 W	3.000	488 x 287 x 103	
2370 AB21L/18/42/75/ML-740 ET 26	8260640	7.500 / 4.200 / 1.800	62 W / 35 W / 15 W	4.000	488 x 287 x 103	
2370 AB21L/100/150/200/ML-730 ET 26	8260740	20.000 / 15.000 / 10.000	166 W / 125 W / 83 W	3.000	705 x 331 x 113	
2370 AB21L/100/150/200/ML-740 ET 26	8260840	20.000 / 15.000 / 10.000	166 W / 125 W / 83 W	4.000	705 x 331 x 113	

Accessories for 2370 LED

product reference	TOC	Description	
2370/42 REDUZIERSTÜCK	8434400	Reduzierstück aus Aluminium. Für Mastzopf Ø 42 mm	Ø 82 x 102 mm

