

## General info


## Technical - Recessed

Indoor ceiling recessed projector with integrated LED sources and direct light emission

|              |                            |
|--------------|----------------------------|
| Ean          | 8021696123981              |
| Item         | GROOVE FI 10W SQUARE 3000K |
| Installation | Recessed (Ceiling)         |
| Guarantee    | 5 years                    |
| Gross weight | 0.33 kg                    |
| Volume       | 0.00117 m <sup>3</sup>     |

## Technical info

|                         |                                                                     |
|-------------------------|---------------------------------------------------------------------|
| Net weight              | 0.27 kg                                                             |
| Insulation class        | II                                                                  |
| Protection index        | IP20                                                                |
| Operating temperature   | 0° ~ +40 °C                                                         |
| Dimmer                  | Non-dimmable, On-Off                                                |
| Power output            | 220-240 V AC 50/60 Hz                                               |
| Power supply            | Separate, included<br>YES (by qualified operators only), electronic |
| Recessed specifications | 100 x 100 - h. ≥ 60 , 7-15                                          |



## Source info

|                        |                                   |
|------------------------|-----------------------------------|
| Integrated source      | Integrated LED module             |
| Replaceable source     | YES (by qualified operators only) |
| Power                  | 10W                               |
| Emission               | Direct                            |
| Max consumption        | max 10,5 W                        |
| Features LED           | LED SMD                           |
| CCT                    | 3000 K                            |
| Duration LED (t. 25°C) | 30000 h                           |
| CRI                    | > 80                              |
| SDCM                   | -                                 |
| Light beam             | 110°                              |
| Light beam flux        | 1200 lm                           |
| Useful light flux      | 710 lm                            |
| Photobiological risk   | 1                                 |
| Standby power          | < 0.50                            |