



## General info

### DECORATIVO - Wall

Indoor wall mounted adjustable lamp with multiple sources, in-built switch, in-built USB port and diffuse and direct light emission

|              |                        |
|--------------|------------------------|
| Ean          | 8021696174808          |
| Item         | BOOK-1 AP NERO         |
| Installation | Wall                   |
| Guarantee    | 5 years                |
| Gross weight | 2 kg                   |
| Volume       | 0.01248 m <sup>3</sup> |

## Technical info

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Net weight            | 1.57 kg                                       |
| Insulation class      | I                                             |
| Protection index      | IP20                                          |
| Operating temperature | 0° ~ +40 °C                                   |
| Dimmer                | Non-dimmable, On-Off                          |
| Power output          | 220-240 V AC 50/60 Hz                         |
| Power supply          | In-built, included                            |
| Adjustability         | YES (by qualified operators only), electronic |
|                       | YES                                           |

## Source info

|                        |                                                  |
|------------------------|--------------------------------------------------|
| Integrated source      | Light bulb (not included), Integrated LED module |
| Replaceable source     | Replaceable (LED: by qualified operators only)   |
| Power                  | G9/LED max 1 x 28W / 3W                          |
| Emission               | Diffuse + Direct                                 |
| Max consupcion         | max 28W / LED 3.0 W                              |
| Features LED           | LED SMD                                          |
| CCT                    | 3000 K                                           |
| Duration LED (t. 25°C) | 15000 h                                          |
| CRI                    | > 80                                             |
| Light beam flux        | 200 lm                                           |
| Useful light flux      | LED 130 lm                                       |
| Photobiological risk   | 2                                                |
| Standby power          | < 0.50                                           |
| Bulb included          | LED INTEGRATO LED 200Lm 3000K                    |