



General info

Technical - Recessed

Indoor ceiling recessed projector with integrated LED sources and direct light emission

Ean	8021696192406
Item	GAME SQUARE 11W 3000K BK WH
Installation	Recessed (Ceiling)
Guarantee	5 years
Gross weight	0.4 kg
Volume	0.001634 m ³

Technical info

Net weight	0.31 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	75 x 75 - h. ≥ 150 , 3-20
Load resistance	IK06
Front protection index	IP40 [DO NOT COVER]
Accessories not included	Dimmable driver

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	11W
Emission	Direct
Max consupcion	max 11,00 W
Features LED	LED COB CREE
CCT	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	5
Light beam	36°
UGR Maximum	< 19
Light beam flux	1100 lm
Useful light flux	1010 lm
Standby power	< 0.50