

## General info

## DECORATIVO - Wall


Indoor wall mounted lamp with integrated LED sources and indirect light emission



|              |                            |
|--------------|----------------------------|
| Ean          | 8021696195728              |
| Item         | COVER AP D15 SQUARE BIANCO |
| Installation | Ceiling, Wall              |
| Guarantee    | 5 years                    |
| Gross weight | 0.57 kg                    |
| Volume       | 0.001792 m³                |

## Technical info

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Net weight            | 0.51 kg                                                             |
| Insulation class      | II                                                                  |
| Protection index      | IP20                                                                |
| Operating temperature | 0° ~ +40 °C                                                         |
| Dimmer                | Non-dimmable, On-Off                                                |
| Power output          | 220-240 V AC 50/60 Hz                                               |
| Power supply          | In-built, included<br>YES (by qualified operators only), electronic |



## Source info

|                        |                                   |
|------------------------|-----------------------------------|
| Integrated source      | Integrated LED module             |
| Replaceable source     | YES (by qualified operators only) |
| Power                  | LED 9,5W                          |
| Emission               | Indirect                          |
| Max consumption        | max 9,50 W                        |
| Features LED           | LED SMD                           |
| CCT                    | 3000 K                            |
| Duration LED (t. 25°C) | 30000 h                           |
| CRI                    | > 90                              |
| Light beam flux        | 830 lm                            |
| Useful light flux      | 470 lm                            |
| Standby power          | < 0.50                            |