



## General info

### DECORATIVO - Hanging

Indoor suspended lamp with multiple integrated LED sources and direct light emission

|              |                       |
|--------------|-----------------------|
| Ean          | 8021696247243         |
| Item         | GEMINI SP D042 OTTONE |
| Installation | Suspension            |
| Guarantee    | 5 years               |
| Gross weight | 2.18 kg               |
| Volume       | 0.02304 m³            |

## Technical info

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Net weight            | 1.29 kg                                                  |
| Insulation class      | I                                                        |
| Protection index      | IP20                                                     |
| Compliance            | CE                                                       |
| Operating temperature | 0° ~ +40 °C                                              |
| Dimmer                | Non-dimmable, On-Off                                     |
| Power output          | 220-240 V AC 50/60 Hz                                    |
| Power supply          | In-built, included                                       |
|                       | Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | LED 38W                                   |
| Emission               | Direct                                    |
| Max consupcion         | max 38,00 W                               |
| Features LED           | LED SMD                                   |
| CCT                    | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 80                                      |
| Light beam             | 130°                                      |
| Light beam flux        | 5100 lm                                   |
| Useful light flux      | 2720 lm                                   |
| Photobiological risk   | 1                                         |
| Standby power          | < 0.50                                    |