



## General info

### DECORATIVO - Wall

Indoor wall recessed adjustable projector with integrated LED sources, in-built switch and direct light emission

|              |                        |
|--------------|------------------------|
| Ean          | 8021696250120          |
| Item         | LITE AP OTTONE         |
| Installation | Recessed (Wall)        |
| Guarantee    | 5 years                |
| Gross weight | 0.5 kg                 |
| Volume       | 0.00081 m <sup>3</sup> |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.34 kg                                                                        |
| Insulation class      | I                                                                              |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz<br>Integrated switch button                              |
| Power supply          | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |
| Adjustability         | YES                                                                            |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | LED 3 W                                   |
| Emission               | Direct                                    |
| Max consupcion         | max 3,00 W                                |
| Features LED           | LED SMD                                   |
| CCT                    | 3000 K                                    |
| Duration LED (t. 25°C) | 20000 h                                   |
| CRI                    | > 80                                      |
| Light beam             | 23°                                       |
| Light beam flux        | 200 lm                                    |
| Useful light flux      | 130 lm                                    |
| Photobiological risk   | 2                                         |
| Standby power          | < 0.50 W                                  |