



## General info

### DECORATIVO - Wall

Indoor wall mounted adjustable lamp with integrated LED sources, in-built switch and direct light emission

|              |                       |
|--------------|-----------------------|
| Ean          | 8021696260679         |
| Item         | BEAN SQUARE AP NICKEL |
| Installation | Wall                  |
| Guarantee    | 5 years               |
| Gross weight | 0.22 kg               |
| Volume       | 0.0008 m <sup>3</sup> |

## Technical info

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Net weight            | 0.18 kg                                       |
| Insulation class      | I                                             |
| Protection index      | IP20                                          |
| Operating temperature | 0° ~ +40 °C                                   |
| Dimmer                | Non-dimmable, On-Off                          |
| Power output          | 220-240 V AC 50/60 Hz                         |
| Power supply          | In-built, included                            |
| Adjustability         | YES (by qualified operators only), electronic |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | LED 3W                                    |
| Emission               | Direct                                    |
| Max consumption        | max 3,00 W                                |
| Features LED           | LED SMD CREE                              |
| CCT                    | 3000 K                                    |
| Duration LED (t. 25°C) | 30000 h                                   |
| CRI                    | > 80                                      |
| Light beam             | 25°                                       |
| Light beam flux        | 280 lm                                    |
| Useful light flux      | 250 lm                                    |
| Photobiological risk   | 2                                         |
| Standby power          | < 0.50                                    |