


General info

Technical - Recessed


Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission



Ean	8021696266558
Item	OFF FI 15W 3000K BK
Installation	Recessed (Ceiling)
Guarantee	5 years
Gross weight	0.57 kg
Volume	0.002052 m³

Technical info

Net weight	0.46 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic, tridonic
Recessed specifications	Ø 100 - h. ≥ 130 , 1-25
Front protection index	IP54
Accessories not included	Dimmable driver, Black reflector



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	15 W
Emission	Direct
Max consupcion	max 15 W
Features LED	LED COB CITIZEN
CCT	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Light beam	50°
UGR Maximum	< 19
Light beam flux	1350 lm
Useful light flux	1085 lm
Standby power	< 0.50 W