


## General info

## Technical - Recessed


Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission



|              |                     |
|--------------|---------------------|
| Ean          | 8021696266565       |
| Item         | OFF FI 15W 4000K BK |
| Installation | Recessed (Ceiling)  |
| Guarantee    | 5 years             |
| Gross weight | 0.57 kg             |
| Volume       | 0.002052 m³         |

## Technical info

|                          |                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------|
| Net weight               | 0.46 kg                                                                                  |
| Insulation class         | II                                                                                       |
| Protection index         | IP20                                                                                     |
| Compliance               | CE                                                                                       |
| Operating temperature    | 0° ~ +40 °C                                                                              |
| Dimmer                   | Non-dimmable, On-Off                                                                     |
| Power output             | 220-240 V AC 50/60 Hz                                                                    |
| Power supply             | Separate, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic |
| Recessed specifications  | Ø 100 - h. ≥ 130 , 1-25                                                                  |
| Front protection index   | IP54                                                                                     |
| Accessories not included | Dimmable driver, Black reflector                                                         |



## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 15 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 15 W                                  |
| Features LED           | LED COB CITIZEN                           |
| CCT                    | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 50°                                       |
| UGR Maximum            | < 19                                      |
| Light beam flux        | 1450 lm                                   |
| Useful light flux      | 1155 lm                                   |
| Standby power          | < 0.50 W                                  |