



General info

Technical - Recessed

Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission

Ean	8021696266596
Item	OFF FI 42W 3000K BK
Installation	Recessed (Ceiling)
Guarantee	5 years
Gross weight	2.08 kg
Volume	0.009396 m ³

Technical info

Net weight	1.85 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic, tridonic
Recessed specifications	Ø 195 - h. ≥ 180 , 1-25
Front protection index	IP54
Accessories not included	Dimmable driver, Black reflector

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	42 W
Emission	Direct
Max consupcion	max 42 W
Features LED	LED COB CITIZEN
CCT	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Light beam	60°
UGR Maximum	< 19
Light beam flux	4150 lm
Useful light flux	3320 lm
Standby power	< 0.50 W