



## General info

### Technical - Recessed

Indoor ceiling recessed adjustable projector with integrated LED sources and direct light emission

|              |                          |
|--------------|--------------------------|
| Ean          | 8021696267920            |
| Item         | NOVA FI 12W 4000K BK     |
| Installation | Recessed (Ceiling, Wall) |
| Guarantee    | 5 years                  |
| Gross weight | 0.62 kg                  |
| Volume       | 0.001563 m <sup>3</sup>  |

## Technical info

|                          |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| Net weight               | 0.54 kg                                                                        |
| Insulation class         | II                                                                             |
| Protection index         | IP20                                                                           |
| Compliance               | CE                                                                             |
| Operating temperature    | 0° ~ +40 °C                                                                    |
| Dimmer                   | Non-dimmable, On-Off                                                           |
| Power output             | 220-240 V AC 50/60 Hz                                                          |
| Power supply             | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |
| Recessed specifications  | Ø 90 - h. ≥ 180 , 3-30                                                         |
| Adjustability            | vert. 0°-90° , orizz. 0°-360°                                                  |
| Accessories not included | Dimmable driver, Narrow beam lens                                              |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 12 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 12 W                                  |
| Features LED           | LED COB PHILIPS                           |
| CCT                    | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | -                                         |
| Light beam             | 38°                                       |
| UGR Maximum            | < 19                                      |
| Light beam flux        | 1100 lm                                   |
| Useful light flux      | 900 lm                                    |
| Standby power          | < 0.50 W                                  |