



General info

Indoor - Suspensions

|              |                     |
|--------------|---------------------|
| Ean          | 8021696321059       |
| Item         | FLAM SP TRASPARENTE |
| Installation | Suspensions         |
| Warranty     | 5 years             |
| Gross weight | 1.25 kg             |
| Volume       | 0.005419 m³         |

Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.79 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | LED 10 W                                  |
| Emission               | Diffuse                                   |
| Max consupcion         | max 10 W                                  |
| Features LED           | LED SMD Bridgelux                         |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°c) | 30000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam flux        | 900 lm                                    |
| Useful light flux      | 610 lm                                    |
| Photobiological risk   | EXEMPT                                    |