


## General info

## Indoor - Wall lamps



|              |                     |
|--------------|---------------------|
| Ean          | 8021696321547       |
| Item         | BALANCE AP D45 NERO |
| Installation | Wall lamps          |
| Guarantee    | 5 years             |
| Gross weight | 1.2 kg              |
| Volume       | 0.005625 m³         |

## Technical info



|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 1.2 kg                                                                         |
| Insulation class      | I                                                                              |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | NO, On-Off                                                                     |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                                    |
|------------------------|------------------------------------|
| Integrated source      | Integrated LED module              |
| Replaceable source     | No                                 |
| Power                  | LED 12 W                           |
| Emission               | Direct                             |
| Max consupcion         | max 12,00 W                        |
| Features LED           | LED SMD                            |
| CCT LED                | 3000 K                             |
| Duration LED (t. 25°C) | 30000 h                            |
| CRI                    | > 90                               |
| Light beam             | 100°                               |
| Light beam flux        | 1450 lm                            |
| Useful light flux      | 980 lm                             |
| Photobiological risk   | 1                                  |
| Bulb included          | 1 - E14 OLIVA 4W 3000K CRI80 SATIN |