

## General info

## Indoor - Table lamps



|              |                  |
|--------------|------------------|
| Ean          | 8021696334998    |
| Item         | MIGNON TL BIANCO |
| Installation | Table lamps      |
| Warranty     | 5 years          |
| Gross weight | 0.4 kg           |
| Volume       | 0.001188 m³      |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.36 kg                                                                        |
| Insulation class      | III                                                                            |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | 1, Touch dimmer                                                                |
| Power output          | 5 V DC                                                                         |
| Power supply          | Required, separate, not included (power charger, output 5 V DC 1 A) electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 5 W               |
| Emission               | Diffuse               |
| Max consupcion         | max 5 W               |
| Features LED           | LED SMD SAMSUNG       |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam flux        | 460 lm                |
| Useful light flux      | 110 lm                |
| Photobiological risk   | EXEMPT                |
| Standby power          | < 0.50 W              |