Specifications

Photo is representative

Eaton 211805

Eaton Moeller series xEffect - AZ MCB. Miniature circuit breaker (MCB), 100A, 2p, C-Char

General specifications	
PRODUCT NAME	Eaton Moeller series xEffect - AZ MCB
CATALOG NUMBER	211805
MODEL CODE	AZ-2-C100
EAN	4015082118051
PRODUCT LENGTH/DEPTH	90 mm
PRODUCT HEIGHT	75 mm
PRODUCT WIDTH	54 mm
PRODUCT WEIGHT	0.46 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 60947-2 EN45545-2 IEC 61373
GLOBAL CATALOG	211805
PRODUCT TYPE	MCB

Powering Business Worldwide

Product specifications

USED WITH	AZ Miniature circuit breaker
AMPERAGE RATING	100 A
VOLTAGE RATING	230 V AC / 400 V AC
FEATURES	Additional equipment possible
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

Resources

APPLICATION NOTES	eaton-quality-standards-for-railway-applications-application-paper-ap003005en-en-us.pdf eaton-maximum-cable-lengths-for-eatons-protective-devices-brochure-br034006en-en-us.pdf
BROCHURES	eaton-pdd-railrolling-stock-brochure-br011002en-en-us.pdf
CHARACTERISTIC CURVE	eaton-mcb-tripping-characteristic-xeffect-az-characteristic-curve.eps eaton-xeffect-az-mcb-characteristic-curve-002.jpg eaton-mcb-xeffect-az-characteristic-curve-002.eps eaton-mcb-current-xeffect-az-characteristic-curve-002.eps eaton-mcb-xeffect-az-characteristic-curve.eps eaton-xeffect-az-mcb-characteristic-curve-004.jpg eaton-mcb-current-xeffect-az-characteristic-curve.eps
DECLARATIONS OF CONFORMITY	eaton-mcb-declaration-of-conformity-eu250431en.pdf
DRAWINGS	eaton-mcb-xeffect-az-dimensions-003.eps eaton-xpole-mmct-mcb-dimensions.jpg eaton-xeffect-az-mcb-3d-drawing.jpg eaton-mcb-faz-xeffect-faz-3d-drawing-002.eps eaton-xeffect-az-mcb-3d-drawing-002.jpg
ECAD MODEL	ETN.AZ-2-C100
INSTALLATION	IL019148ZU

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FRAME	45 mm
POLLUTION DEGREE	2
MOUNTING METHOD	Top-hat rail IEC/EN 60715
DEGREE OF PROTECTION	IP40 (when fitted) IP20
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	18.3 W 18.2 W
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4 kV
ADMISSIBLE BACK-UP FUSE - MAX	200 A gL/gG
TERMINAL PROTECTION	Finger and hand touch safe, DGUV VS3, EN 50274
TERMINALS (TOP AND BOTTOM)	Lift terminals
TRIPPING CHARACTERISTIC	C
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
BUILT-IN DEPTH	75 mm
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED)	50 mm²

INSTRUCTIONS	
MCAD MODEL	DA-CS-az_1pn_2p DA-CD-az_1pn_2p
PEP ECO-PASSPORT	eaton-non-selective-universal-mcb-pep-eato-00259-v0101-en.pdf
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 211805
WIRING DIAGRAMS	eaton-xpole-mmc4-6-m-mcb-wiring-diagram-003.jpg eaton-mcb-xeffect-faz-wiring-diagram-002.eps

- MAX	
CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN	2.5 mm²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX	50 mm²
CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN	2.5 mm²
CURRENT LIMITING CLASS	3
ENCLOSURE WIDTH	90 mm
FREQUENCY RATING - MAX	60 Hz
FREQUENCY RATING - MIN	50 Hz
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	9.1 W
DIRECTION OF INCOMING SUPPLY	As required
WIDTH IN NUMBER OF MODULAR SPACINGS	3
VOLTAGE RATING AT DC	60 V DC (per pole)
VOLTAGE TYPE	AC
OVERVOLTAGE CATEGORY	III
NUMBER OF POLES	Two-pole
LIFESPAN, ELECTRICAL	10000 operations
RELEASE CHARACTERISTIC	C
TYPE	• AZ • Miniature circuit breaker
SPECIAL FEATURES	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
APPLICATION	• Switchgear for industrial and advanced commercial

	applications • xEffect - Switchgear for industrial and advanced commercial applications
MOUNTING WIDTH	27 mm
SELECTIVITY CLASS	3
MOUNTING WIDTH PER POLE	27 mm
NUMBER OF POLES (PROTECTED)	2
NUMBER OF POLES (TOTAL)	2
OPERATIONAL SWITCHING CAPACITY	20 kA
RATED INSULATION VOLTAGE (UI)	440 V
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	100 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	400 V
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 230 V	20 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY (IEC 60947-2)- ICU AT 400 V	20 kA
RATED SWITCHING CAPACITY (IEC/EN 60947-2)	20 kA
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
TERMINAL CAPACITY (CONTROL CABLE)	2.5 mm^2 - 50 mm^2

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.