

DKS 3-13 Dowel clamp 30020

CE 6/2022

Areas of application:

For the single installation of casing pipes (single cable and cable bundles) such as antenna cables, telephone lines and flex s.

Installation Guide:

- Drill a 6mm Ø hole
- Wrap the DKS around the cable
- Insert the DKS into the drill hole

Product details:

Colour	light grey
Content pack/box	200 / 7.200
Clamping range mm	3-13

Mounting and usage instructions:

Cover the cable(s) with the DKS and insert the DKS into a 6 mm drill hole. Drill. Fasten. Done!

Product benefits/properties:

Good cable tension options with the DKS. When laid, the strap is barely visible.

Technical data:

Material	PP, UV stabilised Temperature range: -10 °C up to +85 °C silicon-free Material tested according OVR R14 (LSFOH)
Weight per piece	0,50 g
Max. recd. load	Reference value: DKS 3-13: 99.2 N concrete, 108.72 N solid brick

Breaking load Reference value: DKS 3-13: 248.00 N (24.8 kg) concrete, 271.80 N (27 kg) hollow brick

GTIN (EAN) 9 008439 400201



Schnabl Stecktechnik GmbH, Bahnhofplatz 1, po box 63, 3100 St. Pölten, Austria
Telephone +43 2742 22167-0, office@schnabl.works, www.schnabl.works

