



HAMMER-ON FLANGE CLIP BOTTOM MOUNT STUD SPRING STEEL 3–8 MM FLANGE 11 MM SCREW

CATALOG NUMBER

EM24SM



CERTIFICATIONS



FEATURES

Can be used to support boxes, fixtures or other applications from beam flanges

Captive threaded stud minimizes the need for additional hardware

Assorted attachment points provided to reduce inventory

Requires only a hammer to install

PRODUCT ATTRIBUTES

Article Number: 170530

Material: Spring Steel

Finish: nVent CADDY Armour

Flange Thickness: 3 – 8 mm

Rod Size: M6

Screw Diameter: M6


Screw Length: 11 mm

Static Load 1: 450 N

Static Load 2: 330 N

Static Load 3: 110 N

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500