



Type BSTK (plastic dummy plug)



PRODUCT INFORMATION

The type BSTK dummy plug is made of specially modified polyamide and is available with metric or Pg thread. For instance, it can be used as a temporarily filler for holes currently not required in the control cabinet. IP 65 protection rating can be achieved using an additional type OR O-ring. (O-ring not

included in the delivery)

SPECIFICATIONS

-  Mod. polyamide PA 6
-  -30 – 100 °F Short periods 130 °F
-  IP 54
IP 65 with additional sealing ring, type OR
-  acc. to UL94 HB





Article	Order No.	Color	AG	EH mm	GL mm	Ø mm	MOQ pcs.
BSTK-M12x1,5	83726450	Black	M12x1,5	3.00	6.00	15.00	100
BSTK-M16x1,5	83726452	Black	M16x1,5	3.50	6.00	20.00	100
BSTK-M20x1,5	83726454	Black	M20x1,5	4.00	6.00	24.00	100
BSTK-M25x1,5	83726456	Black	M25x1,5	4.50	8.00	30.00	100
BSTK-M32x1,5	83726458	Black	M32x1,5	4.50	8.00	37.00	100
BSTK-M40x1,5	83726460	Black	M40x1,5	5.50	8.00	46.00	50
BSTK-M50x1,5	83726462	Black	M50x1,5	5.50	10.00	56.00	50
BSTK-M63x1,5	83726464	Black	M63x1,5	4.50	12.00	70.00	50
BSTK-M12x1,5	83726410	Gray	M12x1,5	3.00	6.00	15.00	100
BSTK-M16x1,5	83726412	Gray	M16x1,5	3.50	6.00	20.00	100
BSTK-M20x1,5	83726414	Gray	M20x1,5	4.00	6.00	24.00	100
BSTK-M25x1,5	83726416	Gray	M25x1,5	4.50	8.00	30.00	100
BSTK-M32x1,5	83726418	Gray	M32x1,5	4.50	8.00	37.00	100
BSTK-M40x1,5	83726420	Gray	M40x1,5	5.50	8.00	46.00	50
BSTK-M50x1,5	83726422	Gray	M50x1,5	5.50	10.00	56.00	50
BSTK-M63x1,5 ¹⁾	83726424	Gray	M63x1,5	4.50	12.00	70.00	50
BSTK-Pg 07	83721410	Gray	Pg 07	1.50	6.00	15.00	100
BSTK-Pg 09	83721412	Gray	Pg 09	2.50	6.00	19.00	100
BSTK-Pg 11	83721414	Gray	Pg 11	3.00	6.00	22.00	100
BSTK-Pg 13.5	83721416	Gray	Pg 13.5	3.50	6.00	25.00	100
BSTK-Pg 16	83721418	Gray	Pg 16	3.50	6.00	27.00	100
BSTK-Pg 21	83721420	Gray	Pg 21	3.50	8.00	33.00	100
BSTK-Pg 29	83721422	Gray	Pg 29	3.50	8.00	44.00	100
BSTK-Pg 36	83721424	Gray	Pg 36	5.00	10.00	55.00	50

Type BSTK (plastic dummy plug)

Article	Order No.	Color	AG	EH mm	GL mm	Ø mm	MOQ pcs.
BSTK-Pg 42	83721426	Gray	Pg 42	6.00	10.00	62.00	50
BSTK-Pg 48	83721428	Gray	Pg 48	5.00	12.00	69.00	50
¹) No stock goods, delivery time and minimum order quantities upon request							

MATERIAL PROPERTIES



Mod. polyamide PA 6

THERMAL PROPERTIES

**Temperature / temperature range**

-30 – 100 °F Short periods 130 °F

PROTECTION CLASS

**Protection class**

IP 54

IP 65 with additional sealing ring, type OR

FIRE BEHAVIOR



acc. to UL94 HB

TECHNICAL INFORMATION

**Halogen-free**

CONFORMITY

**RoHS (EC Directive 2011/65/EU)**

All details given in our sales brochures and catalogs, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the products described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information regarding the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or in experiments, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • proID_66358~20220201~890283~suv_bstk_ku