



**Push button 16A 250V~
with built-in indicator
light and quick terminal
connection system
Simon K45**

Ref.: **K304**

BASIC INFORMATION

Indicator function	Sí
Consumption indicator	0,55 mA
No. of possible elements	Half element
Compatibility	Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-03X)
Installation direction	Vertical according to the direction of the mechanisms
Packaging contents	Mechanism and instructions
Remarks	It is not possible to combine 2 narrow button control mechanisms on a Simon 500 Cima-Simon K45 adapter plate
Version	Single
Intensity	16 A
Voltage	250 V~
Type of terminal connection	Fast
Type of mechanism	Tilting

Technical information

Cable section admitted	Up to 1.5 mm
Cable stripping necessary	11 mm
IP rating	20
RAL	Does not have
Manufacturing material	Metallic components with halogen free insulation and thermoplastic caps
Type of product	Standard
Market available	CE

Regulations

Regulations	Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2:2008
-------------	--

Installation and maintenance

Installation type	Suitable for surface and flush mounting
Installable in flush mount junction box	Universal, specific Simon K45 and specific Simon 500 Cima through adaptor (ref.50012088-03X)
Operating temperature range	5 to 40° C
Storage temperature range	-25 to 50° C



www.simonelectric.com



SIMON, S.A.U.

Diputación, 390-392
08013 Barcelona (Spain)
Tel.: +34 93 547 81 81