

NEUTRAL BAR FOR TD DISTRIBUTION BLOCKS, 125 A IEC

CATALOG NUMBER

NB-125A



CERTIFICATIONS



FEATURES

Attaches to four pole distribution blocks for increased wire capacity

Direct electrical connection

Strong mechanical assembly

Transparent protection cover

Halogen free

RoHS compliant

Conforms to EN 45545 obtaining an HL3 classification for chapter R23 and HL2 classification for chapter R22

PRODUCT ATTRIBUTES

Article Number: 563841

Max Current Rating, IEC: 125 A

Short Term Withstand Current (Icw) 1s: 4.5 kA


Peak Short Circuit Current (Ipk): 30 kA

Line Side Number of Connections: 3

Line Side Compact Stranded Wire Size: 10 - 25 mm²

Line Side Stranded Wire Size - Ferrule: 6 – 16 mm²
Load Side Number of Connections: 9
Load Side Compact Stranded Wire Size: 2,5 - 6 mm²
Load Side Stranded Wire Size - Ferrule: 1,5 – 6 mm²
Depth: 37.4 mm
Height: 34.3 mm
Width: 142 mm
Unit Weight: 0.17 kg
For Use With: TD-100-125AL (563830); TD-100-125ALL (563840)
Flammability Rating: UL® 94V-0
Complies With: IEC® 60947-7-1

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--