

FS SPACER CLAMP, 40–63 MM

CATALOG NUMBER

FS40-63



CERTIFICATIONS



FEATURES

Provides support for nVent ERIFLEX Flexibar and insulated braided conductors without damaging the insulation

Ensures correct spacing for optimum cooling

Supports up to four conductors in parallel

Easy to install

Spacers are halogen free

RoHS compliant

PRODUCT ATTRIBUTES

Article Number: 553570

Finish: Electrogalvanized

Material: Steel; Polyamide

Working Temperature: -40 to 130 °C

Flammability Rating: UL® 94HB

Conductor Width: 40 – 63 mm


Height: 95 mm

Length: 166 mm
Hole Size: 8.5 mm
A: 150 mm
Unit Weight: 0.1 kg

ADDITIONAL PRODUCT DETAILS

Recommended distance between supports is 400 mm (15 3/4").

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America	Europe	Europe	APAC
+1.800.753.9221	Netherlands:	Germany:	Shanghai:
Option 1 – Customer Care	+31 800-0200135	800 1890272	+ 86 21 2412 1618/19
Option 2 – Technical Support	France:	Other Countries:	Sydney:
	+33 800 901 793	+31 13 5835404	+61 2 9751 8500