

LED Zubehör

LED accessories



Sensor Kabel, 5 m, 4-Adern, offen/M12 Buchse, A-kodiert

Artikel-Nr.:	200100-04
EAN:	4260556621890
Bestell-Nr.:	200100-04
Modell:	LED2WORK Sensor Kabel 0,34 mm ² , für 24V DC
Bauform:	Sensor Kabel, PUR, schwarz
Kodierung:	A kodiert
Geeignet für:	LED2WORK Leuchten 24V DC, außer RGB und RGB-W
Anzahl:	1
Länge Kabel:	5 m
Kabelenden:	offene Enden, 4 Adern/ M12 Buchse, gerade
Polzahl:	4
Bemessungsspannung:	250V
Strombelastung pro PIN:	4000 mA
Umgebungstemperatur:	-30...+90°C
Durchgangswiderstand:	< 0,005 Ω
Isolationswiderstand:	≥10 ⁸ Ω
Material Kabel:	PUR
Material Griffkörper:	Kunststoff, TPU, BK
Material_Kontaktträger:	Kunststoff, TPU, BK
Material Überwurf:	Metall, CuZn, vernickelt
Material Dichtung:	FPM / FKM
Material Kontakte:	Metall, CuSn, vergoldet
Normen:	IEC 61076-2-101
Befestigung an Leuchte:	Steckverbinder M12 Buchse, gerade
RoHS:	1
UL:	1
Schutzart (montiert):	IP65, IP67, IP68
Gewicht:	200 g
Bruttogewicht:	250 g

Litzenfarben auf dem Bild können zum aktuellen Originalprodukt abweichen.



Sensor cable, 5 m (16,4 ft), open, 4 cores/M12 socket, A-type encoded

Item number:	200100-04
EAN:	4260556621890

Order number:	200100-04
Model:	LED2WORK sensor cable 0,34 mm ² , for 24V DC
Type:	sensor cable, PUR, black
Encoding:	A-type encoded
Suitable for:	LED2WORK 24V DC luminaires, except RGB and RGB-W
Quantity:	1
Length of cable:	5 m (16,4 ft)
Cable ends:	open ends, 4 cores / M12 socket, straight
Number of contacts:	4
Rated voltage:	250V
Current load per PIN:	4000 mA
Operating temperature:	-30... +90°C (-22... 194 °F)
Resistance:	< 0,005 Ω
Insulation resistance:	≥10 ⁸ Ω
Material cable:	PUR
Materials grip body:	plastics, TPU, BK
Material contact carrier:	plastics, TPU, BK
Material cap:	metal, CuZn, nickel-plated
Material seals:	FPM / FKM
Materials contacts:	metal, CuSn, gold-plated
Standards:	IEC 61076-2-101
Gross weight:	connector M12 socket, straight
RoHS:	1
UL:	1
Degree of protection (fitted):	IP65, IP67, IP68
Weight (net):	200 g (~7 oz)
Gross weight:	250 g (~9 oz)

The wire colours in the illustration may differ from the current original product.